

PLASMA PURE

APPLICATIONS

The PlasmaPURE 600 is a brush-style needlepoint ionizer producing positive and negative oxygen ions that neutralize odors and harmful pollutants. This unit is highly versatile as it may be installed in a furnace, an air handling unit, fan coil unit, PTAC, heat pump or ductless split system. The unit is self-contained in a potted ABS enclosure which has molded tabs with mounting holes for fan inlet mounting with screws or magnets. Models are available to accept 12VAC, 24VAC, 120VAC and 230VAC without the use of an external power supply.



KEY FEATURES

- Low maintenance. The PlasmaPURE 600 is designed for continuous operation without requiring replacement parts.
- Cleaning interval. The device should be checked semi-annually to confirm the brushes are clean for maximum output.
- Three year warranty. Free from defects in material and workmanship under normal use when installed, operated and maintained in accordance with manufacturer's instructions.

SPECIFICATIONS

Airflow capacity	2,400 CFM
Pressure drop	Less than 0.01 in. WG
Housing material	ABS
Weight	0.2 lbs
Maximum operating temperature	200 °F (93 °C)
Voltage input	24V AC
Power consumption	Less than 1 watt
Frequency	50/60 hertz

All specifications subject to change without notice.

FIND OUT MORE

Learn more about PlasmaPure. Call 319-435-8851 or visit healthyliving-today.net.

